

Distributed by:



**Corrosion
Control
Equipment
and
Supplies**

Houston Office:
248 McCarty Dr.
Houston, TX 77029-1195
(713) 672-8251
Fax (713) 672-6636

1-800-CLEMTEX
www.clemtex.com
clemtex@clemtex.com

Dallas Branch:

4770 Gretna
Dallas, TX 75207
(214) 631-0584
Fax (214) 631-5824
1-800-BLAST 97

Corpus Christi Branch:

4750 Westway
Corpus Christi, TX 78408
(361) 882-8282
Fax (361) 882-6029




BNP 600 & 720 Mini Blast Rooms - Suction System



Model BNP-720 with 900 CFM Reclaimer and Reverse Pulse Collector

**Clean
Peen
Deburr
Finish**



Cutaway shown

BNP 600 & 720 Mini Blast Rooms deliver efficient, affordable media blasting to clean, peen, deburr, or finish parts.

Common Applications

- Remove rust, mill scale, heat scale, and carbon buildup from metals
- Strip paint, powder coating, plating, and anodizing from parts for rework
- Eliminate burrs, parting lines, flashings, and other defects from castings and injection-molded parts
- Extract residual sand from castings
- Beautify steel, stainless steel, aluminum, brass and other metals with a uniform matte finish
- Etch artwork and lettering into glass, stone, plastics, metal and other materials
- Clean release agents and material buildup from molds

BNP 600 & 720 Suction Cabinets Feature:

Safety

- ✓ Full-length, neoprene-on-fabric gloves resist wear and protect operator.
- ✓ Ceiling-mounted, four-tube fluorescent light fixture with abrasive resistant wire-embedded glass cover cover for extraordinary visibility.
- ✓ Safety interlocks interrupt blasting if either door is opened.
- ✓ Heavy-duty, cam-style latch seals doors tight through years of service.

Productivity

- ✓ Unique Air Logic system (pilot actuated) to maximize air flow to the nozzle.
- ✓ Double-wall, sound-insulated doors.
- ✓ 12-gauge steel all-welded construction, with strength breaks to form a rigid, long-lasting cabinet shell.
- ✓ Large 20" x 30" view window.

Convenience

- ✓ Tilt-out window, for tool-free glass changes in minutes.
- ✓ Pressure regulator, gauge, and electric switch mounted within easy reach.
- ✓ Built-in blow-off gun helps keep dust inside the cabinet, not on your floor.

BNP Blast Gun with Ceramic Nozzle

The BNP blast gun sets the industry standards for performance, versatility, and durability. The ergonomically proven grip reduces operator fatigue and increases productivity. The standard ceramic nozzle is perfect for bead blasting, while the optional tungsten or boron carbide nozzles stand up to hundreds of hours of blasting with today's aggressive abrasives.


Popular Accessories

- Adjustable Vortex Cylinder—recommended for light weight media (std on RP collectors)
- Air-powered Vertical Lift Door
- Alox Kit
- Curtains (black or high visibility white)
- HEPA filter (RP model only)
- Manometer Kit
- Oscillator Assembly
- Timed door release
- 30", 40, and 48" Dia. Turntables
- Work Car & Track Assembly
- Additional operator station
- Additional door set

S P E C I F I C A T I O N S

COMPLETE SYSTEM

Actual space required depends on equipment configurations, options and desired work flow. Allow additional work space for operator and maintenance access.




MEDIA RECLAIMER

The Heart of ZERO's Blasting System

Our exclusive media reclaimers continuously extract dust and debris and return properly sized, usable media to the blast system. The standard reclaimer handles all non-metallic media. For metallic media, specify reduced ID conveying hose.

The suction blast metering valve is infinitely adjustable from fully-closed to wide open, and locks into any setting without tools.

The versatile design of our larger reclaimers lets you quickly adapt the system to your changing needs - add media hoppers, rubber liners, or pull-through dust collection.



BNP BLAST GUN

AIR CONSUMPTION

| BNP GUN | NOZZLE ORIFICE | AIR JET | CFM at 80 PSI | M ³ /Min at 5,5 BAR | MINIMUM RECLAIMER |
|---------|----------------|---------|---------------|--------------------------------|-------------------------------------|
| No. 4 | 5/16" | 1/8" | 21 | 0,60 | 900 CFM (25 m³/m) |
| No. 5 | 5/16" | 5/32" | 32 | 0,90 | 900 CFM (25 m³/m) |
| No. 6 | 3/8" | 3/16" | 48 | 1,35 | 900 CFM (25 m³/m) |
| No. 7 | 7/16" | 7/32" | 62 | 1,76 | 900 CFM (25 m³/m) |
| No. 8 | 1/2" | 1/4" | 85 | 2,41 | 900 CFM (25 m³/m) |

BNP Mini Blast Rooms are furnished with a No. 5 BNP gun. Other sizes and liner materials are available.

ELECTRICAL

(Available with three phase motors only):

900 CFM (25 m³/m) 2HP, 3PH, 60HZ, (1.5KW, 220V, 3PH, 50HZ,);
1200 CFM (34 m³/m) 5HP, 3PH, 60HZ, (3.7KW, 220V, 1PH, 50HZ,);

Other motors and electrical configurations are available to make your system compatible with local power systems.

ORDERING INFORMATION

| Model Number | Reclaim CFM (m ³ /m) | Dust Coll. | 230V Stk. No. | 460V Stk. No. | Ship Wt. lb(kg) |
|------------------|---------------------------------|------------|---------------|---------------|-----------------|
| BNP-600-900 DF | 900 (25) | Dry Filter | 12667 | 12673 | 2,215 (1005) |
| BNP-600-900 RPC | 900 (25) | RPC-2 | 12668 | 12674 | 2,495 (1132) |
| BNP-600-900 RPH | 900 (25) | RPH-2 | 14394 | 14438 | 3,070 (1393) |
| BNP-600-1200 RPH | 1200 (34) | RPH-3 | 14441 | 14442 | 3,825 (1735) |
| BNP-720-900 DF | 900 (25) | Dry Filter | 12652 | 12658 | 2,835 (1420) |
| BNP-720-900 RPC | 900 (25) | RPC-2 | 12653 | 12659 | 3,115 (1286) |
| BNP-720-900 RPH | 900 (25) | RPH-2 | 14396 | 14450 | 3,690 (1674) |
| BNP-720-1200 RPH | 1200 (34) | RPH-3 | 14453 | 14454 | 4,735 (2148) |

Distributed By:

| | | |
|--|--|---|
| BNP600 A - 59" (1499mm) B - 60" (1524mm) C - 81.25" (2064mm) | Model illustrated: BNP-600 with free-standing Reclaimer and RPH Dust Collector | BNP720 A - 72" (1829mm) B - 72.25" (1835mm) C - 91.25" (2318mm) |
|--|--|---|

CABINET

Working Chamber Size


| | |
|---------------|----------------------|
| BNP600 | 56" wide (1422 mm) |
| | 58.5" deep (1486 mm) |
| | 53" high (1346 mm) |
| BNP720 | 69" wide (1753 mm) |
| | 70.5" deep (1778 mm) |
| | 63" high (1600 mm) |

Window Size (safety glass)

| |
|-------------------|
| 30" wide (762 mm) |
| 20" high (508 mm) |

Double swinging doors on right side only. Door interlock system conforms to U.S. government regulations.

Door Opening



| | |
|---------------------|----------------|
| BNP600 | BNP720 |
| A - 55.5" (1410 mm) | 67" (1702 mm) |
| B - 47" (1194 mm) | 58" (1473 mm) |
| C - 21.5" (546 mm) | 22.5" (572 mm) |
| D - 27" (686 mm) | 38" (965 mm) |
| E - 46" (1168 mm) | 54" (1372 mm) |

DUST COLLECTORS

Dry filters are suitable for most industrial applications where the dust collector can be shut off periodically to shake dust from the 100% cotton sateen filter tubes.

Dry filters trap 98% of dust down to 1.0 micron.

Reverse pulse cartridge dust collectors (which trap 99.7% of dust down to 0.5 micron) allow non-stop, high-production blasting. The polyester-cellulose cartridges are automatically pulse cleaned for maximum filter efficiency. Worn cartridges can be replaced in minutes.

| Dry Filters | Reverse Pulse Collector |
|---|---|
| 5 sq ft filter area per tube 900 cfm DF has 40 tubes (200 sq ft) | 235 sq ft filter area per cartridge RPC-2 has 2 cartridges (470 sq ft) RPH-3 has 3 cartridges (705 sq ft) |

Clemco is committed to continuous product improvement. Specifications are subject to change without notice.

Clemco Industries is an ISO 9001 certified company.