

**Distributed by:**



**Corrosion  
Control  
Equipment  
and  
Supplies**

**Houston Office:**  
248 McCarty Dr.  
Houston, TX 77029-1195  
(713) 672-8251  
Fax (713) 672-6636

***1-800-CLEMTEX***  
***www.clemtex.com***  
***clemtex@clemtex.com***

**Dallas Branch:**

4770 Gretna  
Dallas, TX 75207  
(214) 631-0584  
Fax (214) 631-5824  
1-800-BLAST 97

**Corpus Christi Branch:**

4750 Westway  
Corpus Christi, TX 78408  
(361) 882-8282  
Fax (361) 882-6029

# PosiTest<sup>®</sup> DFT

## Coating Thickness Gage

**New**

### *Ideal for...*

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

### *2 Models...*

**Ferrous** for STEEL

**Combo** for ALL METALS



simply  
measures

**DeFelsko<sup>®</sup>**  
*The Measure of Quality*

# PosiTest<sup>®</sup> DFT

## Coating Thickness Gage

Actual Size

### Two Models

- **PosiTest DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**  
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.



### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage

### Specifications

Measurement Range	0 – 40 mils	0 – 1000 $\mu$ m
Accuracy	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2\mu\text{m} + 3\%)$
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
Weight	2.5 oz.	70 g



**Gage Comes Complete** with built-in probe, plastic shims, hard shell storage case, AAA battery, instructions and one (1) year warranty.

**Conforms to:** ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D7091-05/D1400/E376/G12, BS3900-C5, SSPC-PA2 and others. *Certificate of Calibration traceable to NIST available.*