



Houston Office
248 McCarty Dr.
P.O. Box 15214
Houston TX, 77220-5214
(713) 672-8251
Fax (713) 672-6336
Email houston@clemtex.com

1-800-CLEMTEX
www.clemtex.com

Corpus Christi Branch
4750 Westway
P.O. Box 5036
Corpus Christi, TX 78465
(361) 882-8282
Fax (361) 882-6029
Email corpus@clemtex.com

Dallas Branch
4770 Gretna
Dallas, TX 75207
(214) 631-0584
Fax (214) 631-5824
Email dallas@clemtex.com



CLEMCO
The Performance
System

TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

Purpose

4-ply blast hose is used in industrial settings where external scuffing and occasional light vehicle traffic is expected. It can be used with all common blast media.

Description of Operation

Clemco 4-ply blast hose accepts properly sized blast couplings and nozzle holders. The coupled hose can attach to any blast machine fitted with quick coupling connections.

4-ply hose is widely used in shipyards and railyards because it stands up to external abrasions from being dragged about the blast site. The tough outer casing of 4-ply blast hose can even withstand occasional light vehicle traffic without collapsing.

For applications where 4-ply blast hoses are used, a 10- to 15-foot length of Clemco Supa hose can be connected as the last section before the nozzle. This whip hose is easier for the operator to bend and maneuver.

Advantages

- 4-ply hose has a durable outer casing compared to 2-braid and Supa hose
- Inner tube wall of 1/4-inch thick SBR rubber treated with static-dissipating compound
- Four-layer outer casing of cloth and rubber-impregnated fiber winding
- Casing is pin-pricked to prevent formation of air pockets between layers


Description

Durable, reinforced 4-ply blast hose, rated at 175 psi working pressure.



Blast Hose, 4-Ply

Stock No. 23444, 23445, 23446,
23447, 23448, 23449, 23450, 23451,
23452, 23453, 23455, 24750



Options and Accessories

Description	Stock No.
For 1/2-inch 4-ply	
CHE-1/2 aluminum nozzle holder (3/4" thread)	00577
CQA-1/2 aluminum coupling	00599
For 3/4-inch 4-ply	
NHP-1 nylon nozzle holder (contractor thread)	04106
HEP-1 nylon nozzle holder (1-1/4" thread)	07720
CQP-1 nylon coupling	08412
For 1-inch 4-ply	
NHP-2 nylon nozzle holder, (contractor thread)	04127
CQP-2 nylon coupling	21711
For 1-1/4-inch 4-ply	
NHP-3 nylon nozzle holder, (contractor thread)	04128
CQP-3 nylon coupling	08414
For 1-1/2-inch 4-ply	
CFP cplg nozzle holder	07716
FHP cplg nozzle holder	07718
CFPM cplg nozzle holder	07719
CQP-4 nylon coupling	07714

Related Clemco Literature

Contractor Series Catalog	21385
Abrasive Blasting Safety Practices ..	22090
Blast Off 2	09294
Safety Cable TDS	21970

Uncoupled, 4-ply Blast Hose

Description	Stock No.
1/2" ID x 1-3/16" OD* x 25 ft.	23444
1/2" ID x 1-3/16" OD* x 50 ft.	23445
3/4" ID x 1-1/2" OD* x 25 ft.	23446
3/4" ID x 1-1/2" OD* x 50 ft.	23447
3/4" ID x 1-1/2" OD* x 100 ft.	24750
1" ID x 1-7/8" OD* x 25 ft.	23455
1" ID x 1-7/8" OD* x 50 ft.	23448
1" ID x 1-7/8" OD* x 100 ft.	23449
1-1/4" ID x 2-3/32" OD* x 50 ft.	23450
1-1/4" ID x 2-3/32" OD* x 100 ft.	23451
1-1/2" ID x 2-3/8" OD* x 50 ft.	23452
1-1/2" ID x 2-3/8" OD* x 100 ft.	23453

Blast Hose Safety Cables

For 1/2" to 1-1/4" OD hose.....15012
For 1-1/2" to 3" OD hose15013

*OD spec is held for 6 inches from each end.

Color - Black

Ships coiled and shrink wrapped.

Stock No.	Weight	Stock No.	Weight
2344412 lbs	23449109 lbs
2344524 lbs	2345060 lbs
2344618 lbs	23451121 lbs
2344735 lbs	2345265 lbs
2345527 lbs	23453130 lbs
2344854 lbs	2475064 lbs

Authorized Distributor:



ISO 9001:2000 certified. Clemco is committed to continuous product improvement.
Specifications are subject to change without notice.