

Houston Office: 248 McCarty Dr. Houston, TX 77029-1195 (713) 672-8251 Fax (713) 672-6636

1-800-CLEMTEX www.clemtex.com clemtex@clemtex.com Dallas Branch: 4770 Gretna Dallas, TX 75207 (214) 631-0584 Fax (214) 631-5824 1-800-BLAST 97

Corpus Christi Branch: 4750 Westway Corpus Chrisi, TX 78408 (361) 882-8282 Fax (361) 882-6029



TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

Purpose

High-performance, versatile blast cleaning system removes contamination, corrosion, mill scale, and coatings from most surfaces. Produces a uniform surface texture, and creates a surface profile to increase bonding for coatings.

Model 1648 holds 3 cubic feet of abrasive providing 15 minutes of blasting at 100 psi with a No. 6 (3/8-inch) nozzle.

Requirements for Operation

These items are required but not included with this equipment:

- Clean, dry, compressed air of sufficient volume to maintain desired pressure at the nozzle. Refer to Air Consumption Chart in Blast Off 2 booklet (publication stock no. 09294).
- Minimum of 50 psi needed to close the pop-up valve and pressurize the blast machine.
- OSHA-required remote control system that interrupts blasting if operator should lose control of the nozzle when blast machine is pressurized.
- NIOSH-approved, type CE, suppliedair respirator.
- Grade D breathing-air supply as defined by Compressed Gas Association Commodity Specification: G-7.1 (Refer to www.cganet.com).
- Abrasive blast media specifically manufactured for abrasive blasting and appropriate for your application.
- Appropriate blast suit, work boots, hearing and eye protection.

Description

Field-portable, medium-duty, industrial, single-chamber blast machine rated at 150 psi working pressure. Model 1648 has 1-1/4 inch piping and holds 3 cubic feet of media (300 lbs expendable, mineral abrasive). This unit is equipped with FSV abrasive metering valve and remote controls. Complete system includes coupled hose, nozzle, supplied air respirator, and many accessories.

3 Cuft Classic Blast Machine Systems



Description of Operation

The operator controls blasting from a remote control handle at the nozzle. Pressing the handle starts blasting; releasing it stops blasting. The blast machine contains abrasive and meters it into the compressed air stream.

Approvals and Certifications


Clemco's quality management system is ISO 9001-2000 certified.

Blast machine pressure vessel built to American Society of Mechanical Engineers (ASME) specifications for 150-psi working pressure. Vessel is hydrostatically tested and National Board-certified.

Remote control system complies with OSHA regulation 1910.244 (b).

Advantages

- Field-portable, industrial-quality blast machine manufactured to ASME code.
- 1-1/4-inch piping allows up to 50 percent more air flow when compared with 1-inch piping.
- Industrial-quality valves, piping and fittings designed to maximize air flow and minimize energy required to operate the system.
- FSV abrasive metering valve maintains smooth, consistent, adjustable media flow.
- State-of-the-art NIOSH-approved respirator with DLX comfort-fit suspension.



Wt

42

1.5

.5

.5 <.5 <.5 1

> 6 9

9

65 175 205

Model 1648: 3 cuft Blast Machine, Classic with 1-1/4" piping; 150 psi working pressure			Item Description	Stock No.
			Accessory Package	
Item Description	Stock No.	Wt.	1-1/2" Air filter w/ manual 50 ft. x 1-1/4" Supa hose	w/ NHP-2
Without remotes:			and CQPS-2	
with FSV abrasive metering	a valve		Blast hose safety cable	
portable		330	TXP-6 nozzle	
stationary		330	Blast machine screen, 16	
With TLR 300 remotes:			Poly all-weather cover	
and FSV abrasive metering	a valve		Leather gloves, 1 pair	
portable		335	Nylon ties, 8 ea.	
and Manual Quantum metering valve			CQGP-3 gaskets, pk of 1008853 NW-32 nozzle washers, pk of 1091026	
portable23767		325	Abrasive trap screens, (6)	
and Sentinel abrasive metering valve			Helmet outer lenses, pk o	
with ACS (abrasive cut-of	f switch)			1 23
portable		345	Options/Accessories	
stationary	21066	345	Blast machine cover, 16"	02335
			Metering valve, manual Quantum22845 Carbon monoxide alarm, CMS-222894	
Systems				
1648-300-CA11260 475 Includes: 1-1/4" piping, Blast machine 01178, Apollo 600 HP DLX (for use with compressed air) respirator with Clem-Cool Air Conditioner (CCAC), 50 ft.			Ambient Air Pumps	
			CAP-1, sgl operator	
			CAP-4, 4 operators w/ fr	
			CAP-4C, 4 operators w/	
respirator hose, CPF 20 E			Blast suit, heavy cotton/le	
Accessory Package	J		S (08920), M (08921), L	
, ,	02000	485	XXL (24201), XXXL (242	
1648-ACS-CA			Blast suit, seasonal cotto	
			S (22913), M (22914), L	
Conditioner (CCAC), 50 ft			XXL (22917), XXXL (250)22)
Breathing-air filter and Ac		20	Manuals	
•	, ,		Blast Machine without Re	motes06160
1648-300-AA23894 475 Includes: 1-1/4" piping, Blast machine 01178, Apollo 600 LP DLX (for use with ambient air) respirator with Constant Flow Connector (CFC), 50 ft. respirator hose, and Appendent Package			Blast Machine with	
			TLR300 Remotes	
			TLR300 with ACS	
			Sentinel Valve	
and Accessory Package			I	

ISO 9001:2000 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.

© 2009 Clemco Industries Corp. • One Cable Car Drive • Washington, MO 63090 • Phone (636) 239-4300 • Fax (800) 726-7559 Stock No. 24879 Job No. 2324-1106 • Rev. C 06/09