# **Airless Hand and Automatic Spray Guns**

## ■ Airless 1



This lightweight drop-forged, manual spray gun, (for applying various maintenance and decorative finishes) features a stainless steel head and fluid passages, ball-type fluid valve, removable valve assembly, tungsten carbide seat, and built-in diffuser. The thumb-operated safety trigger lock permits one hand locking, unlocking, and triggering. A tip guard is included for added safety. (*Maximum operating pressure is 6000 PSI.*) Part Sheet: 77-2340. (*Spray tip not included. order separately*)

Airless 1M- similar to Airless 1, but designed for the application of abrasives and high viscosity fluids such as plastics, adhesives, sound deadeners, as well as conventional paints and coatings. Fluid head can be rotated 180°, 3/8NPT(f) fluid inlet with a 9/16-18 JIC(m) adapter. Part Sheet 77-2495

#### ■ Model 550



For spraying protective coatings such as lacquers, enamels, waterbased emulsions, mold release agents, and sound deadeners. Spray gun equipped with tip guard, stainless steel fluid passages, and forged aluminum spray gun body. Actuating air pressure is 40-60 PSI. The material body may be installed in any of four positions to facilitate fluid hose connection. Spray nozzle not included, order separately. Mounting hole is 1/2" diameter, furnished with set screw. (Maximum operating pressure is 3000 PSI.)

# ■ 550 Specifications

1/4" NPS (m)
1/4" NPS (m)
1 1/2 lbs.
77-2120

#### ■ Model 570



Same as Model 550, but constructed with larger fluid inlet and passages. Used for spraying heavy materials such as mastics and undercoatings. Spray nozzle not included, order separately. (Maximum operating pressure is 3000 PSI.)

### 570 Specifications

Air Inlet:	1/4" NPS (m)
Fluid Inlet:	1/2" NPT (f)
Weight:	2-1/2 lbs.
Part Sheet:	77-2122

#### Airless accessories

Airless nozzle extensions - attach to airless guns for access to hard-to-reach areas. Available made to order in various lengths. (Gun or tip not included). Contact customer service for details.

#### FLAT TIP ASSEMBLIES FOR AIRLESS GUNS

PART Number	STAMPED Number	ORIFICE (INCHES)	FAN WIDTH (12" FROM SURFACE)
9-1170	9-1170	.011	8-10
9-1180	9-1180	.011	10-12
9-1350	9-1350	.013	8-10
9-1360	9-1360	.013	10-12
9-1380	9-1380	.013	12-14
9-1550	9-1550	.015	8-10
9-1560	9-1560	.015	10-12
9-1590	9-1590	.015	14-16
9-1840	9-1840	.018	10-12
9-1860	9-1860	.018	12-14
9-1890	9-1890	.018	16-18

PART Number	STAMPED Number	ORIFICE (INCHES)	FAN WIDTH (12" FROM SURFACE)
9-2140	9-2140	.021	10-12
9-2180	9-2180	.021	16-18
9-2340	9-2340	.023	10-12
9-2640	9-2640	.026	12-14
9-3120	9-3120	.031	6-8
9-3140	9-3140	.031	12-14
9-3170	9-3170	.031	16-18
9-3180	9-3180	.031	18-20

PART Number	STAMPED Number	ORIFICE (INCHES)	FAN WIDTH (12" FROM SURFACE)
9-3620	9-3620	.036	6-8
9-3640	9-3640	.036	12-14
9-3660	9-3660	.036	16-18
9-3680	9-3680	.036	18-20
9-4340	9-4340	.043	12-14
9-4380	9-4380	.043	18-20
9-6230	9-6230	.062	8-10

